



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/730,660	12/08/2003	Peter D. Karabinis	9301-2IP	4855
20792 7590 11/16/2007 MYERS BIGEL SIBLEY & SAJOVEC PO BOX 37428 RALEIGH, NC 27627			EXAMINER LEE, JOHN J	
			ART UNIT 2618	PAPER NUMBER
			MAIL DATE 11/16/2007	DELIVERY MODE PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

## Office Action Summary

**Application No.**

10/730,660

**Applicant(s)**

KARABINIS, PETER D.

**Examiner**

JOHN J. LEE

**Art Unit**

2618

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) OR THIRTY (30) DAYS, WHICHEVER IS LONGER, FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☒ Responsive to communication(s) filed on 05 September 2007.
- 2a) ☒ This action is **FINAL**.                      2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims

- 4) ☒ Claim(s) 1-42 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 6) ☒ Claim(s) 1-42 is/are rejected.
- 7) ☐ Claim(s) \_\_\_\_\_ is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

### Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All    b) ☐ Some \*    c) ☐ None of:
1. ☐ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- |  |   |
|--|---|
| 1) <input type="checkbox"/> Notice of References Cited (PTO-892)                     | 4) <input type="checkbox"/> Interview Summary (PTO-413)           |
| 2) <input type="checkbox"/> Notice of Draftsperson's Patent Drawing Review (PTO-948) | Paper No(s)/Mail Date. _____                                      |
| 3) <input type="checkbox"/> Information Disclosure Statement(s) (PTO/SB/08)          | 5) <input type="checkbox"/> Notice of Informal Patent Application |
| Paper No(s)/Mail Date _____  | 6) <input type="checkbox"/> Other: _____                          |

## DETAILED ACTION

### *Response to Arguments/Amendment*

1. Applicant's arguments/amendments received on September 05, 2007 have been carefully considered but they are not persuasive because the teaching of all the cited reference reads on all the rejected and amended claims as set forth in the pervious rejection. Therefore, the finality of this Office Action is deemed proper.

Contrary to the assertions at pages 5 - 8 of the Arguments, claims 1, 8, 15, 22, 29, and 36 are not patentable.

During examination, the USPTO must give claims their broadest reasonable interpretation.

Re claims 1, 8, 15, 22, 29, and 36: Applicant argues that the teaching of Regulinski et al. (US 2005/0260948) does not teach the claimed invention "an ancillary terrestrial network that is configured to transmit wireless communications to, and receive wireless communications from, ~~the~~ radiotelephones ~~over~~ the downlink satellite radiotelephone frequency in a time-division duplex mode". However, The Examiner respectfully disagrees with Applicant's assertion that the teaching of Regulinski does not teach the claimed invention. Contrary to Applicant's assertion, the Examiner is of the opinion that the Regulinski teaches an ancillary terrestrial network (terrestrial node (119) in Fig. 11) that is configured to transmit wireless communications to (transmitting wirelessly using shared with the satellite downlink radio frequency to radio telephone as see Fig. 11), and receive wireless communications from (receiving wirelessly using shared with the satellite radio frequency as see in Fig. 11), the radiotelephones (mobile

Art Unit: 2618

terminals) over the downlink satellite radiotelephone frequency (shared with downlink satellite radio frequency) in a time-division duplex mode (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA, and TDMA duplex mode in satellite mobile terminal in Fig. 11) (see Fig. 7, 11, pages 3, paragraphs 50, 58, and pages 8, paragraphs 148 – 149), regarding the claimed limitation. More specifically, communication with terrestrial network via the satellite, each mobile terminal is in communication with the satellite and the terrestrial network via full duplex channel comprises shared downlink satellite channel and shared uplink channel as using same shared satellite frequency, for example a TDMA time slot on a particular frequency allocated on initiation of a communication, and an terrestrial base node configures to transmit downlink the shared satellite frequency to mobile terminal and receives uplink the shared satellite frequency from mobile terminal in a TDMA duplex mode) (Fig. 4, 10 and column 11, lines 9 – 49), regarding the claimed limitation. Moreover, Fig. 7 and 11 teaches the satellite uplink is reused by the second set of base stations in urban areas as a terrestrial uplink, and the satellite downlink as shared the satellite uplink frequency is reused by those base stations as a terrestrial downlink since the satellite uplink and downlink frequency are the same (see Fig. 8 and 11 and pages 6, paragraphs 114 - 121).

Applicant's attention is directed to the rejection below for the reasons as to why this limitation is not patentable.

***Claim Rejections - 35 USC § 102***

Art Unit: 2618

2. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(e) the invention was described in (1) an application for patent, published under section 122(b), by another filed in the United States before the invention by the applicant for patent or (2) a patent granted on an application for patent by another filed in the United States before the invention by the applicant for patent, except that an international application filed under the treaty defined in section 351(a) shall have the effects for purposes of this subsection of an application filed in the United States only if the international application designated the United States and was published under Article 21(2) of such treaty in the English language.

3. **Claims 1-4, 8-11, 15-18, 22-25, 29-32, and 36-39** are rejected under 35 U.S.C. 102(e) as being anticipated by Regulinski et al. (US 2005/0260948).

Regarding **claim 1**, Regulinski teaches a satellite radiotelephone system (Fig. 1). Regulinski teaches that a space-based component (satellite (4) in Fig. 1) that is configured to receive wireless communications from radiotelephones (2 in Fig. 11) (satellite (4) wirelessly receives signal or communication frequency from the mobile terminal) in a satellite footprint (Fig. 11 teaches satellite footprint, also Fig. 4a) over an uplink satellite radiotelephone frequency (uplink satellite radio frequency in Fig. 1) and to transmit wireless communications (downlink wireless communication frequency see Fig. 11) to the radiotelephones (2 in Fig. 11) over a downlink satellite radiotelephone frequency (downlink satellite radio frequency in Fig. 1) (Fig. 11 and pages 3, paragraphs 50, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a communication). Regulinski teaches that an ancillary terrestrial network (terrestrial node (119) in Fig. 11) that is configured to transmit wireless communications (wirelessly transmitting to downlink radio frequency) to, and receive wireless

communications (wirelessly receiving uplink radio frequency) from, the radiotelephones (mobile terminals) over the downlink satellite radiotelephone frequency (downlink satellite radio frequency) in a time-division (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (Fig. 11, pages 3, paragraphs 50, 58, and pages 8, paragraphs 148 - 149, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a communication, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 2**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the ancillary terrestrial network also is configured to transmit wireless communications to (terrestrial node (119) transmits wireless communication channels to mobile terminals in Fig. 11), and receive wireless communications from, the radiotelephones over the uplink satellite radiotelephone frequency in a time-division (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (Fig. 11, pages 3, paragraphs 50, 58, and pages 8, paragraphs 148 - 149, where teaches for communication via the satellite

network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 3**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the time-division (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) includes a frame (Fig. 6) including a plurality of slots (a plurality of time slots in Fig. 7), wherein at least a first one of the slots is used to transmit wireless communications to the radiotelephones over the downlink satellite radiotelephone frequency (Fig. 7 teaches one of the slots (frequency bond comprising time slots) is used to transmit wirelessly communications to mobile terminals over the downlink radio frequency) (see pages 4, paragraphs 80 – 84, where teaches each satellite generates an array of beams covering a footprint beneath the satellite, each beam including a number of different frequency channels and time slots) and wherein at least a second one of the slots is used to receive wireless communications from the radiotelephones over the downlink satellite radiotelephone frequency (Fig. 9 teaches second one of the slots (frequency bond) is used to receive wirelessly communications to mobile terminals over the downlink radio frequency) (Fig. 9, 10, pages 3, paragraphs 50 and pages 4, paragraphs 80 – 81, where teaches for

Art Unit: 2618

communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 4**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the downlink satellite radiotelephone frequency comprises a downlink satellite radiotelephone frequency band (downlink satellite radio frequency band in Fig. 9) and wherein the ancillary terrestrial network (119 in Fig. 11) is configured to transmit wireless communications to, and receive wireless communications from, the radiotelephones (terrestrial downlink and uplink frequency band) over the downlink satellite radiotelephone frequency band (downlink satellite radio frequency band Fig. 9, 10) in a time-division duplex mode (Fig. 9, 10, pages 3, paragraphs 50 and pages 8, paragraphs 143, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency band allocated on initiation of a communication, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 8**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that an ancillary terrestrial component (terrestrial node



(119) in Fig. 11) for a satellite radiotelephone system (Fig. 1) that includes a space-based component (satellite (4) in Fig. 1) that is configured to receive wireless communications from radiotelephones (2 in Fig. 11) (satellite (4) wirelessly receives signal or communication frequency from the mobile terminal) in a satellite footprint (Fig. 11 teaches satellite footprint, also Fig. 4a) over an uplink satellite radiotelephone frequency (uplink satellite radio frequency in Fig. 1) and to transmit wireless communications (downlink wireless communication frequency see Fig. 11) to the radiotelephones (2 in Fig. 11) over a downlink satellite radiotelephone frequency (downlink satellite radio frequency in Fig. 1) (Fig. 11 and pages 3, paragraphs 50, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call). Regulinski teaches that the ancillary terrestrial component (terrestrial node (119) in Fig. 11) comprises an electronics system (electronics system in Fig. 1 and pages 4, paragraphs 87) that is configured to transmit wireless communications to (wirelessly transmitting to downlink radio frequency), and receive wireless communications (wirelessly receiving uplink radio frequency) from, the radiotelephones (mobile terminals) over the downlink satellite radiotelephone frequency (downlink satellite radio frequency) in a time-division (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (Fig. 11, pages 3, paragraphs 50, 58, and pages 8, paragraphs 148 - 149, where

teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 9**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the electronic system also is configured to transmit wireless communications to, and receive wireless communications from, the radiotelephones over the uplink satellite radiotelephone frequency in a time-division (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (Fig. 11, pages 3, paragraphs 50, 58, and pages 8, paragraphs 148 - 149, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a communication, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 10**, Regulinski teaches all the limitation as discussed in claims 1 and 8. Furthermore, Regulinski teaches that the time-division (see pages 10, paragraphs

185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) includes a frame (Fig. 6) including a plurality of slots (a plurality of time slots in Fig. 7), wherein at least a first one of the slots is used to transmit wireless communications to the radiotelephones over the downlink satellite radiotelephone frequency (Fig. 7 teaches one of the slots (frequency bond comprising time slots) is used to transmit wirelessly communications to mobile terminals over the downlink radio frequency) (see pages 4, paragraphs 80 – 84, where teaches each satellite generates an array of beams covering a footprint beneath the satellite, each beam including a number of different frequency channels and time slots) and wherein at least a second one of the slots is used to receive wireless communications from the radiotelephones over the downlink satellite radiotelephone frequency (Fig. 9 teaches second one of the slots (frequency bond) is used to receive wirelessly communications to mobile terminals over the downlink radio frequency) (Fig. 9, 10, pages 3, paragraphs 50 and pages 4, paragraphs 80 – 81, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 11**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the downlink satellite radiotelephone frequency comprises a downlink satellite radiotelephone frequency band (downlink satellite radio frequency band in Fig. 9) and wherein the electronics system (119 in Fig. 11) is configured to transmit wireless communications to, and receive wireless communications from, the radiotelephones (terrestrial downlink and uplink frequency band) over the downlink satellite radiotelephone frequency band (downlink satellite radio frequency band Fig. 9, 10) in a time-division duplex mode (Fig. 9, 10, pages 3, paragraphs 50 and pages 8, paragraphs 143, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency band allocated on initiation of a communication, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 15**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that an electronics system (mobile terminal or base station) that is configured to transmit wireless communications to a space-based component (satellite (4) in Fig. 1) over an uplink satellite radiotelephone frequency (satellite (4) wirelessly receives signal or communication frequency from the mobile terminal) and to receive wireless communications (uplink wireless communication frequency see Fig. 11) from the space-based component (satellite (4) in Fig. 1) over a downlink satellite radiotelephone frequency (downlink satellite radio frequency in Fig.

11) (Fig. 11 and pages 3, paragraphs 50, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel to mobile terminal and uplink channel from mobile terminal, for example a TDMA time slot on a particular frequency allocated on initiation of a communication). Regulinski teaches that the electronics system (terrestrial node or mobile terminal in Fig. 11) further configured to transmit wireless communications to (wirelessly transmitting to uplink radio frequency), and receive wireless communications from (wirelessly receiving downlink radio frequency), an ancillary terrestrial component (119 in Fig. 11) over the downlink satellite radiotelephone frequency (downlink satellite radio frequency) in a time-division (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (Fig. 11, pages 3, paragraphs 50, 58, and pages 8, paragraphs 148 - 149, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 16**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the electronic system also is configured to transmit

Art Unit: 2618

wireless communications to, and receive wireless communications from, the ancillary terrestrial component over the uplink satellite radiotelephone frequency in a time-division (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (Fig. 11, pages 3, paragraphs 50, 58, and pages 8, paragraphs 148 - 149, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite or base station via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a communication, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 17**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the time-division (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) includes a frame (Fig. 6) including a plurality of slots (a plurality of time slots in Fig. 7), wherein at least a first one of the slots is used to transmit wireless communications to the ancillary terrestrial component (base station or mobile terminal in Fig. 11) over the downlink satellite radiotelephone frequency (Fig. 7 teaches one of the slots (frequency bond comprising time slots) is used to transmit wirelessly communications to base station and mobile

terminal over the downlink radio frequency) (see pages 4, paragraphs 80 – 84, where teaches each satellite generates an array of beams covering a footprint beneath the satellite, each beam including a number of different frequency channels and time slots) and wherein at least a second one of the slots is used to receive wireless communications from the ancillary terrestrial component (base station or mobile terminal in Fig. 11) over the downlink satellite radiotelephone frequency (Fig. 9 teaches second one of the slots (frequency band) is used to receive wirelessly communications to mobile terminals over the downlink radio frequency) (Fig. 9, 10, pages 3, paragraphs 50 and pages 4, paragraphs 80 – 81, where teaches for communication via the satellite network and base station, each mobile terminal is in communication with satellite or base station via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a communication, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 18**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the downlink satellite radiotelephone frequency comprises a downlink satellite radiotelephone frequency band (downlink satellite radio frequency band in Fig. 9) and wherein the electronics system (mobile terminal or base station in Fig. 11) also is configured to transmit wireless communications to, and receive wireless communications from, the ancillary terrestrial component (base station or mobile terminal in Fig. 11) (terrestrial downlink and uplink frequency band) over the downlink

satellite radiotelephone frequency band (downlink satellite radio frequency band Fig. 9, 10) in a time-division duplex mode (Fig. 9, 10, pages 3, paragraphs 50 and pages 8, paragraphs 143, where teaches for communication via the satellite network and base station, each mobile terminal is in communication with satellite or base station via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency band allocated on initiation of a communication, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 22**, Regulinski teaches a satellite radiotelephone communication (Fig. 1). Regulinski teaches that receiving wireless communications (receiving uplink communication in Fig. 11) at a space-based component (satellite (4) in Fig. 1) from radiotelephones (2 in Fig. 11) (satellite (4) wirelessly receives signal or communication frequency from the mobile terminal) in a satellite footprint (Fig. 11 teaches satellite footprint, also Fig. 4a) over an uplink satellite radiotelephone frequency (uplink satellite radio frequency in Fig. 1) (Fig. 11 and pages 3, paragraphs 50, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a communication). Regulinski teaches that transmitting wireless communications (Fig. 11 teaches satellite transmits wireless communication frequency to mobile terminal) from the space-based component (satellite (4) in Fig. 1) to the radiotelephones (2 in Fig. 11)



Art Unit: 2618

over a downlink radiotelephone frequency (Fig. 11 and pages 3, paragraphs 50, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel for satellite transmits wireless communication channels to mobile terminal and uplink channel for mobile terminal transmits wireless communication channels to satellite, for example a TDMA time slot on a particular frequency allocated on initiation of a communication). Regulinski teaches that transmitting wireless communications from an ancillary terrestrial network (terrestrial node (119) transmits wireless communication channels to mobile terminals in Fig. 11) to the radiotelephones and transmitting wireless communications (wirelessly transmitting to downlink radio frequency) from the radiotelephones (mobile terminal has a dual mode for recognizing satellite channels and terrestrial network channels) to the ancillary terrestrial network (terrestrial node (119) in Fig. 11) over the downlink satellite radiotelephone frequency in a time-division (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (Fig. 11, pages 3, paragraphs 50, 58, and pages 8, paragraphs 148 - 149, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a communication, and an terrestrial base node configures to transmit

downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 23**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that transmitting wireless communications from the ancillary terrestrial network (terrestrial node (119) transmits wireless communication channels to mobile terminals in Fig. 11) to the radiotelephones (112 in Fig. 11) and transmitting wireless communications from the radiotelephones to the ancillary terrestrial network (Fig. 11) over the uplink satellite radiotelephone frequency in a time-division duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) (Fig. 11, pages 3, paragraphs 50, 58, and pages 8, paragraphs 148 - 149, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 24**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the time-division duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite

system could be CDMA and the terrestrial system is TDMA/FDMA) includes a frame (Fig. 7) including a plurality of slots (Fig. 7 teaches frequency band having a plurality of slots), wherein at least a first one of the slots is used to transmit wireless communications from the ancillary terrestrial network to the radiotelephones over the downlink satellite radiotelephone frequency (Fig. 7 teaches one of the slots (frequency band comprising time slots) is used to transmit wirelessly communications to mobile terminals over the downlink radio frequency from the ancillary terrestrial network) (see pages 4, paragraphs 80 – 84, where teaches each ancillary terrestrial base station generates wireless communication frequency band including a plurality of frames having a plurality of slots wherein downlink slots) and wherein at least a second one of the slots is used to transmit wireless communications from the radiotelephones to the ancillary terrestrial network over the downlink satellite radiotelephone frequency (Fig. 9 teaches second one of the slots (frequency band) is used to receive wirelessly communications to mobile terminals over the downlink radio frequency) (Fig. 9, 10, pages 3, paragraphs 50 and pages 4, paragraphs 80 – 81, where teaches for communication via the satellite network or terrestrial base station, each mobile terminal is in communication with satellite or base station via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency (a plurality of time slots) to mobile terminal and receives uplink the radio frequency (a plurality of time slots) from mobile terminal in a TDMA duplex mode).

Regarding **claim 25**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the downlink satellite radiotelephone frequency comprises a downlink satellite radiotelephone frequency band (downlink satellite radio frequency band in Fig. 9) and wherein the method further comprises transmitting wireless communications from the ancillary terrestrial network (119 in Fig. 11) to the radiotelephones (terrestrial downlink and uplink frequency band) and transmitting wireless communications from the radiotelephones to the ancillary terrestrial network (terrestrial downlink and uplink frequency band) over the downlink satellite radiotelephone frequency band (downlink satellite radio frequency band Fig. 9, 10) in a time-division duplex mode (Fig. 9, 10, pages 3; paragraphs 50 and pages 8, paragraphs 143, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency band allocated on initiation of a communication, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 29**, Regulinski teaches that transmitting wireless communications from an ancillary terrestrial network (terrestrial node (119) transmits wireless communication channels to mobile terminals in Fig. 11) to radiotelephones (Fig. 11 teaches mobile terminal has a dual mode for recognizing satellite channels and terrestrial network channels) and receiving wireless communications from the radiotelephones (wirelessly transmitting to uplink radio frequency) at the ancillary

terrestrial network (terrestrial node (119) in Fig. 11) over a downlink satellite radiotelephone frequency in a time-division duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) (Fig. 11, pages 3, paragraphs 50, 58, and pages 8, paragraphs 148 - 149, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a communication, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 30**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that transmitting wireless communications from the ancillary terrestrial network (terrestrial node (119) transmits wireless communication channels to mobile terminals in Fig. 11) to the radiotelephones (112 in Fig. 11) and receiving wireless communications from the radiotelephones at the ancillary terrestrial network (Fig. 11) over an uplink satellite radiotelephone frequency in a time-division duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) (Fig. 11, pages 3, paragraphs 50, 58, and pages 8, paragraphs 148 - 149, where teaches for communication via the satellite network, each mobile terminal is in

communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 31**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the time-division duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) includes a frame (Fig. 7) including a plurality of slots (Fig. 7 teaches frequency band having a plurality of slots), wherein at least a first one of the slots is used to transmit wireless communications from the ancillary terrestrial network to the radiotelephones over the downlink satellite radiotelephone frequency (Fig. 7 teaches one of the slots (frequency bond comprising time slots) is used to transmit wirelessly communications to mobile terminals over the downlink radio frequency from the ancillary terrestrial network) (see pages 4, paragraphs 80 – 84, where teaches each ancillary terrestrial base station generates wireless communication frequency band including a plurality of frames having a plurality of slots wherein downlink slots) and wherein at least a second one of the slots is used to receive wireless communications from the radiotelephones at the ancillary terrestrial network over the downlink satellite radiotelephone frequency (Fig. 9 teaches second one of the slots (frequency bond) is used to transmit wirelessly communications from mobile

terminals over the downlink radio frequency to terrestrial base station) (Fig. 9, 10, pages 3, paragraphs 50 and pages 4, paragraphs 80 – 81, where teaches for communication via the satellite network or terrestrial base station, each mobile terminal is in communication with satellite or base station via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency (a plurality of time slots) to mobile terminal and receives uplink the radio frequency (a plurality of time slots) from mobile terminal in a TDMA duplex mode).

Regarding **claim 32**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the downlink satellite radiotelephone frequency comprises a downlink satellite radiotelephone frequency band (downlink satellite radio frequency band in Fig. 9) and wherein the transmitting comprises transmitting wireless communications from the ancillary terrestrial network (119 in Fig. 11) to the radiotelephones (terrestrial downlink and uplink frequency band) and receiving wireless communications from the radiotelephones at the ancillary terrestrial network (terrestrial downlink and uplink frequency band) over the downlink satellite radiotelephone frequency band (downlink satellite radio frequency band Fig. 9, 10) in a time-division duplex mode (Fig. 9, 10, pages 3, paragraphs 50 and pages 8, paragraphs 143, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency band allocated on initiation of a communication, and an terrestrial base node configures to transmit

downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 36**, Regulinski teaches that receiving wireless communications from an ancillary terrestrial network (terrestrial node (119) transmits wireless communication channels to mobile terminals in Fig. 11) at radiotelephones (Fig. 11 teaches mobile terminal has a dual mode for recognizing satellite channels and terrestrial network channels) and transmitting wireless communications from the radiotelephones (wirelessly transmitting to uplink radio frequency) to the ancillary terrestrial network (terrestrial node (119) in Fig. 11) over a downlink satellite radiotelephone frequency in a time-division duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) (Fig. 11, pages 3, paragraphs 50, 58, and pages 8, paragraphs 148 - 149, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a communication, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 37**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that receiving wireless communications from the ancillary terrestrial network (terrestrial node (119) transmits wireless communication



channels to mobile terminals in Fig. 11) at the radiotelephones (112 in Fig. 11) and transmitting wireless communications from the radiotelephones to the ancillary terrestrial network (119 in Fig. 11) over an uplink satellite radiotelephone frequency in a time-division duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) (Fig. 11, pages 3, paragraphs 50, 58, and pages 8, paragraphs 148 - 149, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claim 38**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the time-division duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) includes a frame (Fig. 7) including a plurality of slots (Fig. 7 teaches frequency band having a plurality of slots), wherein at least a first one of the slots is used to receive wireless communications from the ancillary terrestrial network at the radiotelephones over the downlink satellite radiotelephone frequency (Fig. 7 teaches one of the slots (frequency bond comprising

time slots) is used to transmit wirelessly communications to mobile terminals over the downlink radio frequency from the ancillary terrestrial network) (see pages 4, paragraphs 80 – 84, where teaches each ancillary terrestrial base station generates wireless communication frequency band including a plurality of frames having a plurality of slots wherein downlink slots) and wherein at least a second one of the slots is used to transmit wireless communications from the radiotelephones to the ancillary terrestrial network over the downlink satellite radiotelephone frequency (Fig. 9 teaches second one of the slots (frequency band) is used to transmit wirelessly communications from mobile terminals over the downlink radio frequency to terrestrial base station) (Fig. 9, 10, pages 3, paragraphs 50 and pages 4, paragraphs 80 – 81, where teaches for communication via the satellite network or terrestrial base station, each mobile terminal is in communication with satellite or base station via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency (a plurality of time slots) to mobile terminal and receives uplink the radio frequency (a plurality of time slots) from mobile terminal in a TDMA duplex mode).

Regarding **claim 39**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the downlink satellite radiotelephone frequency comprises a downlink satellite radiotelephone frequency band (downlink satellite radio frequency band in Fig. 9) and wherein the receiving comprises receiving wireless communications from the ancillary terrestrial network (119 in Fig. 11) at the radiotelephone (terrestrial downlink and uplink frequency band), and transmitting

wireless communications from the radiotelephones to the ancillary terrestrial network (terrestrial downlink and uplink frequency band) over the downlink satellite radiotelephone frequency band (downlink satellite radio frequency band Fig. 9, 10) in a time-division duplex mode (Fig. 9, 10, pages 3, paragraphs 50 and pages 8, paragraphs 143, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency band allocated on initiation of a communication, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

***Claim Rejections - 35 USC § 103***

4. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

5. **Claims 5, 12, 19, 26, 33, and 40** are rejected under 35 U.S.C. 103(a) as being unpatentable over Regulinski.

Regarding **claims 5, 12, and 19**, Regulinski teaches that the time-division duplex mode (TDMA uplink and downlink mode) includes a frame (channel frame) including a plurality of slots (Fig. 7 teaches each satellite generates an array of beams covering a

footprint beneath the satellite, each beam including a number of different frequency channels and time slots), wherein a first number of the slots (Fig. 7) is used to transmit wireless communications (satellite downlink frequency band comprises a plurality of slots) to the radiotelephones (2 in Fig. 11) over the downlink satellite radiotelephone frequency (Fig. 7 teaches satellite downlink frequency) and wherein a second number of the slots (Fig. 7) is used to receive wireless communications (satellite uplink frequency band comprises a plurality of slots) from the radiotelephones over the downlink satellite radiotelephone frequency (Fig. 7 teaches satellite frequency bands), wherein the first number is greater than the second number (pages 6, paragraphs 110 – 112 and Fig. 1, where teaches satellite or base station is dynamically allocated the channels based on channel request from receiver desired, means that receiver desired a lot of data stream for video demand, and it is inherently transmitting channels (slots) is greater than receiving channels (slots), also oppositely as the receiver desired to transmit the data, such that pictures, video, text, it is inherently transmitting channels (slots) is greater than receiving channels (slots)).

Regulinski does not exactly disclose the limitation “the first (downlink) number (slots) is greater than the second (uplink) number (slots)”. However, this would have been obvious to one having ordinary skill in the art at the time of Applicant’s invention, because the Regulinski teaches dynamically channel/frequency allocation of uplink and downlink frequencies used by a number of terrestrial stations and the satellite network is performed (see page 6, paragraphs 110 - 112 and Fig. 1), more specifically, satellite or base station is dynamically allocated the channels based on channel request from receiver

desired, means that receiver desired a lot of data stream for video demand, and it is obviously transmitting channels (slots) is greater than receiving channels (slots), also oppositely as the receiver desired to transmit the data, such that pictures, video, text, it is inherently transmitting channels (slots) is greater than receiving channels (slots), regarding the claimed limitation, provide the motivation to achieve optimal channel allocation for wireless communication units in order to improve communication reliability.

Regarding **claims 26, 33, and 40**, Regulinski teaches all the limitation as discussed in claim 5. Furthermore, Regulinski further teaches that the time-division duplex mode (TDMA uplink and downlink mode) includes a frame (channel frame in Fig. 7) including a plurality of slots (Fig. 7 teaches each satellite generates an array of beams covering a footprint beneath the satellite, each beam including a number of different frequency channels and time slots), wherein a first number of the slots (Fig. 7) is used to transmit wireless communications (ancillary terrestrial base station downlink frequency band comprises a plurality of slots) from the ancillary terrestrial network (119 in Fig. 11) to the radiotelephones (2 in Fig. 11) over the downlink satellite radiotelephone frequency (Fig. 7 teaches satellite downlink frequency) and wherein a second number of the slots (Fig. 7) is used to transmit wireless communications (uplink frequency band of the base station comprises a plurality of slots) from the radiotelephones to the ancillary terrestrial network (119 in Fig. 11) over the downlink satellite radiotelephone frequency (Fig. 7 teaches satellite frequency bands), wherein the first number is greater than the second number (pages 6, paragraphs 110 – 112 and Fig. 1, where teaches satellite or base

station is dynamically allocated the channels based on channel request from receiver desired, means that receiver desired a lot of data stream for video demand, and it is inherently transmitting channels (slots) is greater than receiving channels (slots), also oppositely as the receiver desired to transmit the data, such that pictures, video, text, it is inherently transmitting channels (slots) is greater than receiving channels (slots)).

6. **Claims 6, 7, 13, 14, 20, 21, 27, 28, 34, 35, 41, and 42** are rejected under 35 U.S.C. 103(a) as being unpatentable over Regulinski in view of Balachandran et al. (US 7,142,580).

Regarding **claims 6, 13, and 20**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the time-division (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) includes a frame (Fig. 6) including a plurality of slots (a plurality of time slots in Fig. 7), wherein at least a first one of the slots is used to transmit wireless communications to the radiotelephones over the downlink satellite radiotelephone frequency (Fig. 7 teaches one of the slots (frequency bond comprising time slots) is used to transmit wirelessly communications to mobile terminals over the downlink radio frequency) (see pages 4, paragraphs 80 – 84, where teaches each satellite generates an array of beams covering a footprint beneath the satellite, each beam including a number of different frequency channels and time slots) and wherein at least a second one of the slots is used to receive

wireless communications from the radiotelephones over the downlink satellite radiotelephone frequency (Fig. 9 teaches second one of the slots (frequency bond) is used to receive wirelessly communications to mobile terminals over the downlink radio frequency) (Fig. 9, 10, pages 3, paragraphs 50 and pages 4, paragraphs 80 – 81, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regulinski does not specifically disclose the limitation “transmit wireless communications to the radiotelephones over the downlink satellite radiotelephone frequency using EDGE modulation or protocol, and the slots is used to receive wireless communications from the radiotelephones over the downlink satellite radiotelephone frequency using GPRS modulation or protocol”. However, Balachandran supportly teaches the limitation “transmit wireless communications to the radiotelephones over the downlink satellite radiotelephone frequency using EDGE modulation or protocol (the EDGE technology provides wireless radio signals communication (downlink and uplink) between mobile terminals and base station via satellite for optimization techniques that is using a standard GPRS/EGPRS or EDGE protocol see column 6, lines 65 – column 7, lines 10, Fig. 2, and column 7, lines 48 - 56), and the slots is used to receive wireless communications from the radiotelephones over the downlink satellite radiotelephone

frequency using GPRS modulation or protocol (column 5, lines 59 – column 6, lines 7 and Fig. 2, where teaches program for implementing the GSM/EGPRS protocol on the base station communicating with mobile terminals via satellite)”. It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the Regulinski’s system as taught by Balachandran, provide the motivation to achieve improving network performance for using EGPRS or EDGE protocol for communication with mobile terminal and base station via satellite.

Regarding **claims 27, 34, and 41**, Regulinski and Balachandran teach all the limitation as discussed in claim 6. Furthermore, Regulinski further teaches that the time-division duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) includes a frame (Fig. 7) including a plurality of slots (a plurality of time slots in Fig. 7), wherein at least a first one of the slots is used to transmit wireless communications from the ancillary terrestrial network (119 in Fig. 11) to the radiotelephones (112 in Fig. 11) over the downlink satellite radiotelephone frequency (Fig. 7 teaches one of the slots (frequency bond comprising time slots) is used to transmit wirelessly communications to mobile terminals over the downlink radio frequency) (see pages 4, paragraphs 80 – 84, where teaches each satellite generates an array of beams covering a footprint beneath the satellite, each beam including a number of different frequency channels and time slots) and wherein at least a second one of the slots is used to receive wireless communications at the ancillary terrestrial network from the



radiotelephones over the downlink satellite radiotelephone frequency (Fig. 9 teaches second one of the slots (frequency bond) is used to receive wirelessly communications to mobile terminals over the downlink radio frequency) (Fig. 9, 10, pages 3, paragraphs 50 and pages 4, paragraphs 80 – 81, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regarding **claims 7, 14, and 21**, Regulinski teaches all the limitation as discussed in claim 1. Furthermore, Regulinski teaches that the time-division duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) includes a frame (Fig. 7) including a plurality of slots (a plurality of time slots in Fig. 7), wherein at least a first one of the slots is used to transmit wireless communications to the radiotelephones over the downlink satellite radiotelephone frequency (Fig. 7 teaches one of the slots (frequency bond comprising time slots) is used to transmit wirelessly communications to mobile terminals over the downlink radio frequency) (see pages 4, paragraphs 80 – 84, where teaches each satellite generates an array of beams covering a footprint beneath the satellite, each beam including a number of different frequency channels and time slots) and wherein at least a second one of the slots is used to receive wireless communications

from the radiotelephones over the downlink satellite radiotelephone frequency (Fig. 9 teaches second one of the slots (frequency bond) is used to receive wirelessly communications to mobile terminals over the downlink radio frequency) (Fig. 9, 10, pages 3, paragraphs 50 and pages 4, paragraphs 80 – 81, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

Regulinski does not specifically disclose the limitation “transmit wireless communications to the radiotelephones over the downlink satellite radiotelephone frequency using first modulation or protocol is more spectrally efficient than using second modulation or protocol that the slots is used to receive wireless communications from the radiotelephones over the downlink satellite radiotelephone frequency”.

However, Balachandran supportly teaches the limitation “transmit wireless communications to the radiotelephones over the downlink satellite radiotelephone frequency using first modulation or protocol (the EDGE technology provides wireless radio signals communication (downlink and uplink) between mobile terminals and base station via satellite for optimization techniques that is using a standard EDGE protocol see column 6, lines 65 – column 7, lines 10, Fig. 2, and column 7, lines 48 - 56) is more spectrally efficient than using second modulation or protocol (column 5, lines 59 –

column 6, lines 7 and Fig. 2, where teaches program for implementing the GSM/EGPRS or GPRS protocol on the base station communicating with mobile terminals via satellite) that the slots is used to receive wireless communications from the radiotelephones over the downlink satellite radiotelephone frequency” (see Fig. 2, column 9, lines 62 – column 10, lines 26, and column 2, lines 19 – 31, where teaches EDGE (first modulation or protocol) provides greater spectral efficiencies than other modulation or protocol such that GPRS). It would have been obvious to one having ordinary skill in the art at the time the invention was made to modify the Regulinski’s system as taught by Balachandran, provide the motivation to achieve improving network performance, increase data rates and network capacity, for using EDGE protocol for communication with mobile terminal and base station via satellite.

Regarding **claims 28, 35, and 42**, Regulinski and Balachandran teach all the limitation as discussed in claim 7. Furthermore, Regulinski further teaches that the time-division duplex mode (TDMA duplex mode in satellite mobile terminal in Fig. 11) (see pages 10, paragraphs 185, where teaches TDMA/FDMA satellite system and CDMA terrestrial system, also satellite system could be CDMA and the terrestrial system is TDMA/FDMA) includes a frame (Fig. 7) including a plurality of slots (a plurality of time slots in Fig. 7), wherein at least a first one of the slots is used to transmit wireless communications from the ancillary terrestrial network (119 in Fig. 11) to the radiotelephones (112 in Fig. 11) over the downlink satellite radiotelephone frequency (Fig. 7 teaches one of the slots (frequency bond comprising time slots) is used to transmit wirelessly communications to mobile terminals over the downlink radio frequency) (see

Art Unit: 2618

pages 4, paragraphs 80 – 84, where teaches each satellite generates an array of beams covering a footprint beneath the satellite, each beam including a number of different frequency channels and time slots) and wherein at least a second one of the slots is used to transmit wireless communications from the radiotelephones to the ancillary terrestrial network over the downlink satellite radiotelephone frequency (Fig. 9 teaches second one of the slots (frequency bond) is used to receive wirelessly communications to mobile terminals over the downlink radio frequency) (Fig. 9, 10, pages 3, paragraphs 50 and pages 4, paragraphs 80 – 81, where teaches for communication via the satellite network, each mobile terminal is in communication with satellite via full duplex channel comprises a downlink channel and uplink channel, for example a TDMA time slot on a particular frequency allocated on initiation of a call, and an terrestrial base node configures to transmit downlink the radio frequency to mobile terminal and receives uplink the radio frequency from mobile terminal in a TDMA duplex mode).

### ***Conclusion***

Any response to this action should be mailed to:

Commissioner of Patents and Trademarks  
Washington, D.C. 20231  
Or P.O. Box 1450  
Alexandria VA 22313

or faxed (571) 273-8300, (for formal communications intended for entry)

Art Unit: 2618


Or: (703) 308-6606 (for informal or draft communications, please label "PROPOSED" or "DRAFT").

Hand-delivered responses should be brought to USPTO Headquarters, Alexandria, VA.

Any inquiry concerning this communication or earlier communications from the examiner should be directed to **John J. Lee** whose telephone number is **(571) 272-7880**. He can normally be reached Monday-Thursday and alternate Fridays from 8:30am-5:00 pm. If attempts to reach the examiner are unsuccessful, the examiner's supervisor, **Edward Urban**, can be reached on **(571) 272-7899**. Any inquiry of a general nature or relating to the status of this application should be directed to the Group receptionist whose telephone number is (703) 305-4700.

J.L  
November 8, 2007

John J Lee

  
**EDWARD F. URBAN**  
SUPERVISORY PATENT EXAMINER  
TECHNOLOGY CENTER 2600